

Project:		Type:
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

LED REFLECTORS

BR30

5 CCT Selectable

ORDERING INFORMATION

Order code: 69374

Model number: BR30/8W/5CCT/STD UPC: 069549026889

Case quantity:

PHYSICAL DATA

BR30 Shape: E26 Base: Heat sink color: White

PERFORMANCE DATA

Watts (W): 8 Volts (VAC): 120

Colour temperature (K)1: 2 7000/3 000/3 500/4 000/5 000

Lumen output (Im)2: Efficacy (Im/W): 80 CRI: Life L70 (h)3: 25 000 **Dimming:** Phase cut Beam angle (°): 105 0.93 Power factor: Frequency (Hz): 60

Operating temp. range: -20 °C to 45 °C / -4 °F to 113 °F

Typical colour temperature range: +/- 5 %.

Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.

LUMEN SPECIFICATION TABLE

2 70	00 K	3 000 K		3 500 K		4 000 K		5 000 K	
Lumen output (Im)	Efficacy (Im/W)								
757	95	826	103	888	111	893	112	853	107

DEFAULT PROGRAMMING

2 700 K

COMPATIRI E DIMMERS1

COMINATIBLE DIMINIENC					
Brand	Model				
LUTRON	PD-5NE, PD-6WCL, DVCL-153P, CTCL-153P, DVCL-253P, DVRP-253-WH, SELV-300P, MACL-153P, AYCL-253P				
COOPER	RRD-6NA-WH, AAL06, SLC03P				
LEVITON	IPL06, 6674, DSL06-1ZL, IPE04-1LZ, DDMX1				
LEGRAND	RH703PTUTC				

¹ This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Standard recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

DIMENSIONS

3 3/4" (95 mm)























