



# GE LED Tubes

Complete. Innovative. Trusted.



**current**  
powered by GE



# Why switch to GE LED tubes?

LED Tubes are the fast and easy way to upgrade to LED. With GE's UL Type A, Type B and UL Type C options, you can choose the best solution for your needs.



**2.3X longer life**  
(70K vs. 30K hrs.)



**Uses 43% less energy**  
(18W and 2600 lumens  
vs LFL 32W and 2800 lumens)



**Better quality of light**  
(Instant-On)

## Which LED tube is right for you?

### GE's Integrated LED Tube (UL Type A)

Easy Plug & Play Performance



Uses existing ballast

Quickest installation

Lowest installation cost

Limited dimming

System compatibility  
depends on LFL ballast

### GE's Ballast Bypass LED Tube (UL Type B)

Simplest system direct  
wiring to mains



Uses no external driver or ballast

Eliminates compatibility issues

Excellent efficacy and additional  
maintenance savings

Highest install cost

Requires in-line fuse & socket kit  
Additional safety precaution required

### GE's Remote Driver LED Tube (UL Type C)

Best Performance



Uses external driver, providing  
expanded performance capabilities

Excellent efficacy

Controllable dimming system

Requires LED driver

Medium installation cost



### Complete Offering

GE offers a **broader** and **deeper** LED Tubes assortment than leading competitors.

### Innovative Designs

High-performance solutions for demanding market needs.

### Trusted Experience

GE invented the first linear fluorescent in 1938, and has transferred that leadership to LED tubes.



*What features does GE offer versus the leading competitors?*

**More**  
total tube  
options

**More**  
glass tubes

**Only GE** offers  
Assembled  
in USA


**Highest  
Lumen**  
options in T8 & T5

**No  
Compromise**  
Right brightness,  
type, and material per  
application

**Wider Beam  
Angle**  
Distributes light better  
and eliminates  
dark spots

**Special  
projects &  
Shorter lead  
times**

**Bright Light**  
Provides high light  
output for high-bay  
or demanding  
applications



Statements based on product information on leading competitor public USA websites.

# GE makes updating *Simpler*



## Refit Solutions from GE.

It's never been easier to upgrade from linear fluorescents to GE's LED tubes. With GE's expanding offering, there are efficient solutions for many popular applications.


Integrated, ballast bypass and remote driver technology in 2, 3, 4 & 8 ft lengths and U-tubes

Shatter-resistant plastic option to prevent breakage and downtime


Glass options fully illuminate fixture with 270° light distribution



UL Type A



UL Type B



UL Type C





Linear Fluorescent lighting is the most prevalent light source among Commercial and Industrial buildings. LED Tube conversions are the perfect fit for any industry.

Healthcare



Commercial Office



Manufacturing



Government



Retail



Education

For additional information on all LED Tube offerings go to: <http://products.currentbyge.com>

## LED replacement tubes

### Integrated Plastic Tubes - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty	MOL (In)	Initial Lumens	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
<b>Integrated 4ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)</b>																
T8	G13	18	31550	LED18ET8/4/830	25	48	2450	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	18	93133	LED18ET8/4/835	25	48	2550	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	18	93135	LED18ET8/4/840	25	48	2550	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	18	93140	LED18ET8/4/850	25	48	2650	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	15	62399	LED15ET8/4/830	25	48	2150	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	15	62401	LED15ET8/4/835	25	48	2250	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	15	62402	LED15ET8/4/840	25	48	2250	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	15	62409	LED15ET8/4/850	25	48	2350	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	15	62410	LED15ET8/4/865	25	48	2350	6500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF
	G13	12	61218	LED12ET8/4/830	25	48	1750	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	12	61223	LED12ET8/4/835	25	48	1800	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	12	61271	LED12ET8/4/840	25	48	1800	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	12	61327	LED12ET8/4/850	25	48	1900	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	12	61329	LED12ET8/4/865	25	48	1900	6500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF
<b>Integrated 3ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	12	31554	LED12ET8/3/830	25	36	1500	3000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF
	G13	12	26544	LED12ET8/3/835	25	36	1550	3500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF
	G13	12	26625	LED12ET8/3/840	25	36	1600	4000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF
	G13	12	26627	LED12ET8/3/850	25	36	1650	5000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF
<b>Integrated 2ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	9	31557	LED9ET8/2/830	25	24	1350	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	9	26635	LED9ET8/2/835	25	24	1350	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	9	26648	LED9ET8/2/840	25	24	1400	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
	G13	9	26676	LED9ET8/2/850	25	24	1400	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF
<b>Integrated U6 Plastic Tubes</b>																
	G13	13	43120	LED13ET8/U6/830	12	22.5	1800	3000K	80+			50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	13	43125	LED13ET8/U6/835	12	22.5	1850	3500K	80+			50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	13	43129	LED13ET8/U6/840	12	22.5	1900	4000K	80+			50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	13	43130	LED13ET8/U6/850	12	22.5	1900	5000K	80+			50,000	Yes	Yes	Damp	Instant or PRS Ballast

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

## LED replacement tubes Integrated Glass Tubes - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
<b>Integrated 4 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
T8	G13	18	35767	LED18ET8/G/4/830	20	48	2400	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	18	35768	LED18ET8/G/4/835	20	48	2500	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	18	35769	LED18ET8/G/4/840	20	48	2500	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	18	35772	LED18ET8/G/4/850	20	48	2600	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	18	35773	LED18ET8/G/4/865	20	48	2600	6500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	15	35790	LED15ET8/G/4/830	20	48	2100	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	35791	LED15ET8/G/4/835	20	48	2200	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	35793	LED15ET8/G/4/840	20	48	2200	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	35797	LED15ET8/G/4/850	20	48	2300	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	35798	LED15ET8/G/4/865	20	48	2300	6500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	13.5	21309	LED13ET8G4/830US	20	48	1900	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast- Assembled in USA
	G13	13.5	21344	LED13ET8G4/835US	20	48	2000	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast- Assembled in USA
	G13	13.5	21373	LED13ET8G4/840US	20	48	2000	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast- Assembled in USA
	G13	13.5	21377	LED13ET8G4/850US	20	48	2000	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast- Assembled in USA
	G13	12	43284	LED12ET8/G/4/830	20	48	1700	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	12	43288	LED12ET8/G/4/835	20	48	1750	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	12	43291	LED12ET8/G/4/840	20	48	1750	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	12	43293	LED12ET8/G/4/850	20	48	1850	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	10	34277	LED10ET8/G/4/830	20	48	1550	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	10	34279	LED10ET8/G/4/835	20	48	1600	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	10	34280	LED10ET8/G/4/840	20	48	1600	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	10	34282	LED10ET8/G/4/850	20	48	1650	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
<b>Integrated 4 ft 50K Value LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	14	34283	LED14ET8/G/4/830	20	48	1950	3000K	80+			50,000	-	Yes	Damp	Instant or PRS Ballast
	G13	14	34289	LED14ET8/G/4/835	20	48	2000	3500K	80+			50,000	-	Yes	Damp	Instant or PRS Ballast
	G13	14	34291	LED14ET8/G/4/840	20	48	2100	4000K	80+			50,000	-	Yes	Damp	Instant or PRS Ballast
	G13	14	34300	LED14ET8/G/4/850	20	48	2150	5000K	80+			50,000	-	Yes	Damp	Instant or PRS Ballast
<b>Integrated 4 ft Value LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	15	35896	LED15ET8/835-V6P	6	48	1750	3500K	80+			36,000	-	Yes	Damp	Instant or PRS Ballast
	G13	15	35900	LED15ET8/840-V6P	6	48	1750	4000K	80+			36,000	-	Yes	Damp	Instant or PRS Ballast
	G13	15	35911	LED15ET8/850-V6P	6	48	1800	5000K	80+			36,000	-	Yes	Damp	Instant or PRS Ballast
	G13	15	35913	LED15ET8/865-V6P	6	48	1800	6500K	80+			36,000	-	Yes	Damp	Instant or PRS Ballast
<b>Integrated 3 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	11	35783	LED11ET8/G/3/830	20	36	1450	3000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	11	35784	LED11ET8/G/3/835	20	36	1500	3500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	11	35788	LED11ET8/G/3/840	20	36	1500	4000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	11	35789	LED11ET8/G/3/850	20	36	1600	5000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast
<b>Integrated 2 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	8	35775	LED8ET8/G/2/830	20	24	1300	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	8	35776	LED8ET8/G/2/835	20	24	1350	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	8	35778	LED8ET8/G/2/840	20	24	1350	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	8	35779	LED8ET8/G/2/850	20	24	1400	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast

## Integrated Glass Tubes with reveal® TriGain™ Technology - Type A

<b>Integrated 4 ft High CRI with reveal® TriGain™ Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	15	34307	LED15ET8/G/4/935		20	48	2150	3500K	90		70,000	-	Yes	Damp	Available in March
	G13	15	34313	LED15ET8/G/4/940		20	48	2200	4000K	90		70,000	-	Yes	Damp	Available in March
	G13	15	34316	LED15ET8/G/4/950		20	48	2250	5000K	90		70,000	-	Yes	Damp	Available in March
<b>Integrated 3 ft High CRI with reveal® TriGain™ Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	11	34323	LED11ET8/G/3/935		20	36	1500	3500K	90		70,000	-	Yes	Damp	Available in March
	G13	11	34326	LED11ET8/G/3/940		20	36	1500	4000K	90		70,000	-	Yes	Damp	Available in March
	G13	11	34332	LED11ET8/G/3/950		20	36	1600	5000K	90		70,000	-	Yes	Damp	Available in March
<b>Integrated 2 ft High CRI with reveal® TriGain™ Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	9	34337	LED9ET8/G/2/935		20	24	1300	3500K	90		70,000	-	Yes	Damp	Available in March
	G13	9	34341	LED9ET8/G/2/940		20	24	1300	4000K	90		70,000	-	Yes	Damp	Available in March
	G13	9	34342	LED9ET8/G/2/950		20	24	1400	5000K	90		70,000	-	Yes	Damp	Available in March

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

# UL 1993 Environmental Requirements for LED LAMPS  
 Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
 Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.  
 Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

## LED replacement tubes Integrated Glass Tubes - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
<b>Integrated 4 ft LED Glass T5 HO Tubes (operates on Instant Start or Program Start Ballast)</b>																
T5	G5	25.5	19203	LED26ET5/G/4/830	20	46	3650	3000K	80+			50,000	Yes	Yes	Damp	Requires T5 HO Ballast
	G5	25.5	19221	LED26ET5/G/4/835	20	46	3750	3500K	80+			50,000	Yes	Yes	Damp	Requires T5 HO Ballast
	G5	25.5	19227	LED26ET5/G/4/840	20	46	3800	4000K	80+			50,000	Yes	Yes	Damp	Requires T5 HO Ballast
	G5	25.5	19348	LED26ET5/G/4/850	20	46	3900	5000K	80+			50,000	Yes	Yes	Damp	Requires T5 HO Ballast
	G5	25.5	19488	LED26ET5/G/4/865	20	46	3800	6500K	80+			50,000	-	Yes	Damp	Requires T5 HO Ballast
<b>Integrated 2 ft LED Glass T5 HO Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G5	11	34413	LED11ET5/G/2/830	20	22	1500	3000K	80+			50,000	-	Yes	Damp	Requires T5 HO Ballast
	G5	11	34417	LED11ET5/G/2/835	20	22	1550	3500K	80+			50,000	-	Yes	Damp	Requires T5 HO Ballast
	G5	11	34418	LED11ET5/G/2/840	20	22	1600	4000K	80+			50,000	-	Yes	Damp	Requires T5 HO Ballast
	G5	11	34424	LED11ET5/G/2/850	20	22	1600	5000K	80+			50,000	-	Yes	Damp	Requires T5 HO Ballast
<b>Integrated 4 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G5	13	34351	LED13ET5G4/830HE	20	46	1900	3000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	13	34354	LED13ET5G4/835HE	20	46	1950	3500K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	13	34355	LED13ET5G4/840HE	20	46	2000	4000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	13	34367	LED13ET5G4/850HE	20	46	2000	5000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
<b>Integrated 3 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G5	10	34371	LED10ET5G3/830HE	20	34	1500	3000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	10	34376	LED10ET5G3/835HE	20	34	1550	3500K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	10	34401	LED10ET5G3/840HE	20	34	1600	4000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	10	34402	LED10ET5G3/850HE	20	34	1600	5000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
<b>Integrated 2 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G5	7	34403	LED7ET5/G2/830HE	20	22	1000	3000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	7	34404	LED7ET5/G2/835HE	20	22	1100	3500K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	7	34411	LED7ET5/G2/840HE	20	22	1150	4000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	7	34412	LED7ET5/G2/850HE	20	22	1150	5000K	80+			50,000	-	Yes	Damp	Requires T5 HE Ballast

## Ballast Bypass Glass Tubes - Type B

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
<b>Ballast Bypass- 4 ft LED Glass Tubes</b>																
T8	G13	15	34435	LED15BT8/G4/830	120-277	20	48	2000	3000K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
	G13	15	31919	LED15BT8/G4/835	120-277	20	48	2050	3500K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	15	31933	LED15BT8/G4/840	120-277	20	48	2100	4000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	15	31935	LED15BT8/G4/850	120-277	20	48	2100	5000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
<b>Ballast Bypass- 3 ft LED Glass Tubes</b>																
	G13	13	34472	LED13BT8/G4/830	120-277	20	36	1600	3000K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
	G13	13	34474	LED13BT8/G4/835	120-277	20	36	1700	3500K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
	G13	13	34477	LED13BT8/G4/840	120-277	20	36	1750	4000K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
	G13	13	34478	LED13BT8/G4/850	120-277	20	36	1750	5000K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
<b>Ballast Bypass- 2 ft LED Glass Tubes</b>																
	G13	8	34468	LED8BT8/G2/830	120-277	20	24	950	3000K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
	G13	8	32125	LED8BT8/G2/835	120-277	20	24	1000	3500K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	8	32133	LED8BT8/G2/840	120-277	20	24	1000	4000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	8	32134	LED8BT8/G2/850	120-277	20	24	1100	5000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
<b>Ballast Bypass- U6 LED Glass Tubes</b>																
	G13	12	31919	LED13BT8/U6/830	120-277	20	36	1800	3000K	80+		50,000	-	Yes	Damp	Available in April
	G13	12	31919	LED13BT8/U6/835	120-277	20	36	1850	3500K	80+		50,000	-	Yes	Damp	Available in April
	G13	12	31933	LED13BT8/U6/840	120-277	20	36	1900	4000K	80+		50,000	-	Yes	Damp	Available in April
	G13	12	31935	LED13BT8/U6/850	120-277	20	36	1900	5000K	80+		50,000	-	Yes	Damp	Available in April

## In-Line Fuse & Socket Kit - Type B

Order Code	Description	Kit Content
32075	BT8-2L-KIT/NS	1 Fuse (1A), 2 Pre-wired sockets, Prewired quick disconnect.
32083	BT8-3L-KIT/NS	1 Fuse (1A), 3 Pre-wired sockets, Prewired quick disconnect.
32084	BT8-4L-KIT/NS	1 Fuse (1A), 4 Pre-wired sockets, Prewired quick disconnect.

### Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.



## LED replacement tubes

### Remote Plastic Tubes - Type C

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
<b>Remote Plastic 4 ft LED Tubes (Operates on Remote Driver)</b>																
T8	G13	18	94381	LED21T8/4/835		10	48	2650	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	94382	LED21T8/4/840		10	48	2750	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	94383	LED21T8/4/850		10	48	2850	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	26059	LED21T8/4/865		10	48	2750	6500K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38954	LED15T8/4/830		10	48	1950	3000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38957	LED15T8/4/835		10	48	2000	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38958	LED15T8/4/840		10	48	2050	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38962	LED15T8/4/850		10	48	2100	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38964	LED15T8/4/865		10	48	2050	6500K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
<b>Remote Plastic 3 ft LED Tubes (Operates on Remote Driver)</b>																
	G13	16	82343	LED18T8/3/835		10	36	1800	3500K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	16	82345	LED18T8/3/840		10	36	1800	4000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	16	82346	LED18T8/3/850		10	36	1800	5000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	99692	LED15T8/3/830		20	36	1850	3000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	99693	LED15T8/3/835		20	36	1900	3500K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	99694	LED15T8/3/840		20	36	1950	4000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	99695	LED15T8/3/850		20	36	1950	5000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
<b>Remote Plastic 2 ft LED Tubes (Operates on Remote Driver)</b>																
	G13	8	65706	LED9T8/2/835		20	24	1100	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	8	65707	LED9T8/2/840		20	24	1150	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	8	65711	LED9T8/2/850		20	24	1150	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	8	92997	LED9T8/2/865		20	24	1000	5000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
<b>Remote Plastic LED U Tubes (Operates on Remote Driver)</b>																
	G13	12	28084	LED14T8/U/835		15	22.5	1700	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G13	12	28164	LED14T8/U/840		15	22.5	1700	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver

#### Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.  
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

# LED replacement tubes

## Remote Glass Tubes - Type C

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
<b>Remote 4ft LED Glass Tubes (Operates on Remote Driver)</b>																
T8	G13	18	62428	LED21T8/G/4/835	20	48	2600	3500K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62485	LED21T8/G/4/840	20	48	2700	4000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62487	LED21T8/G/4/850	20	48	2800	5000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62406	LED21T8/G/4/835HL	20	48	2750	3500K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62407	LED21T8/G/4/840HL	20	48	2800	4000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62408	LED21T8/G/4/850HL	20	48	2800	5000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	18	91475	LED21T8/G/4/830US	20	48	2600	3000K	80+			70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	18	91496	LED21T8/G/4/835US	20	48	2600	3500K	80+			70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	18	91497	LED21T8/G/4/840US	20	48	2600	4000K	80+			70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	18	91498	LED21T8/G/4/850US	20	48	2600	5000K	80+			70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	15	99696	LED15T8/G/4/830US	20	48	1950	3000K	80+			70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	15	99697	LED15T8/G/4/835US	20	48	2050	3500K	80+			70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	15	99698	LED15T8/G/4/840US	20	48	2100	4000K	80+			70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	15	99699	LED15T8/G/4/850US	20	48	2100	5000K	80+			70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	13	38944	LED15T8/G/4/830	20	48	1850	3000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	13	38945	LED15T8/G/4/835	20	48	1900	3500K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	13	38950	LED15T8/G/4/840	20	48	1950	4000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	13	38951	LED15T8/G/4/850	20	48	2050	5000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	13	38952	LED15T8/G/4/865	20	48	1950	6500K	80+			70,000	-	Yes	Damp	Requires Driver
	G13	10	76194	LED12T8/G/4/830	20	48	1550	3000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	10	76264	LED12T8/G/4/835	20	48	1600	3500K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	10	76265	LED12T8/G/4/840	20	48	1650	4000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	10	76271	LED12T8/G/4/850	20	48	1650	5000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	10	76278	LED12T8/G/4/865	20	48	1600	6500K	80+			70,000	-	Yes	Damp	Requires Driver
<b>Remote 3ft LED Glass Tubes (Operates on Remote Driver)</b>																
	G13	13	99687	LED15T8/G/3/830	20	36	1800	3000K	80+			70,000	-	Yes	Damp	Requires Driver
	G13	13	99688	LED15T8/G/3/835	20	36	1850	3500K	80+			70,000	-	Yes	Damp	Requires Driver
	G13	13	99689	LED15T8/G/3/840	20	36	1900	4000K	80+			70,000	-	Yes	Damp	Requires Driver
	G13	13	99691	LED15T8/G/3/850	20	36	1900	5000K	80+			70,000	-	Yes	Damp	Requires Driver
	G13	16	38257	LED18T8/G/3/830	20	36	1800	3000K	80+			70,000	-	Yes	Damp	Requires Driver
	G13	16	38258	LED18T8/G/3/835	20	36	1800	3500K	80+			70,000	-	Yes	Damp	Requires Driver
	G13	16	38260	LED18T8/G/3/840	20	36	1900	4000K	80+			70,000	-	Yes	Damp	Requires Driver
	G13	16	38261	LED18T8/G/3/850	20	36	1900	5000K	80+			70,000	-	Yes	Damp	Requires Driver
<b>Remote 2ft LED Glass Tubes (Operates on Remote Driver)</b>																
	G13	8	38933	LED9T8/G/2/830	20	24	1000	3000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	8	38935	LED9T8/G/2/835	20	24	1000	3500K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	8	38936	LED9T8/G/2/840	20	24	1100	4000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	8	38939	LED9T8/G/2/850	20	24	1100	5000K	80+			70,000	Yes	Yes	Damp	Requires Driver
	G13	8	38943	LED9T8/G/2/865	20	24	1000	6500K	80+			70,000	-	Yes	Damp	Requires Driver
<b>Remote 8ft LED Glass Tubes (Operates on Remote Driver)</b>																
	Fo8	30	62326	LED36T8/G/8/830	20	96	4200	3000K	80+			50,000	-	Yes	Damp	Requires Driver - Assembled in USA
	Fo8	30	62327	LED36T8/G/8/835	20	96	4400	3500K	80+			50,000	-	Yes	Damp	Requires Driver - Assembled in USA
	Fo8	30	62329	LED36T8/G/8/840	20	96	4400	4000K	80+			50,000	-	Yes	Damp	Requires Driver - Assembled in USA
	Fo8	30	62349	LED36T8/G/8/850	20	96	4400	5000K	80+			50,000	-	Yes	Damp	Requires Driver - Assembled in USA
<b>Remote Glass U6 Tubes (Operates on Remote Driver)</b>																
	G13	13	43131	LED15T8/G/U6/830	12	22.5	1700	3000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G13	13	43135	LED15T8/G/U6/835	12	22.5	1800	3500K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G13	13	43143	LED15T8/G/U6/840	12	22.5	1800	4000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G13	13	43145	LED15T8/G/U6/850	12	22.5	1800	5000K	80+			50,000	Yes	Yes	Damp	Requires Driver

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
 # UL 1993 Environmental Requirements for LED LAMPS  
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.  
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

# LED replacement lamps

## Remote Glass Tubes - Type C

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
<b>Remote 4ft LED Glass T5 HO Tubes (Operates on Remote Driver)</b>																
T5	G5	31	91973	LED36T5/G/4/830	20	46	4300	3000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91976	LED36T5/G/4/835	20	46	4400	3500K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91977	LED36T5/G/4/840	20	46	4400	4000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91997	LED36T5/G/4/850	20	46	4700	5000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	31	92006	LED36T5/G/4/865	20	46	4700	6500K	80+			50,000	-	Yes	Damp	Requires Driver
<b>Remote 2ft LED Glass T5 HO Tubes (Operates on Remote Driver)</b>																
	G5	13	76150	LED15T5/G/2/830	20	22	1800	3000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	13	76164	LED15T5/G/2/835	20	22	1850	3500K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	13	76129	LED15T5/G/2/840	20	22	1900	4000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	13	76167	LED15T5/G/2/850	20	22	1900	5000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	13	76192	LED15T5/G/2/865	20	22	1900	6500K	80+			50,000	-	Yes	Damp	Requires Driver
<b>Remote 4ft LED Glass T5 HE Tubes (Operates on Remote Driver)</b>																
	G5	15	34176	LED15T5/G4/830HE	20	46	1900	3000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	15	34182	LED15T5/G4/835HE	20	46	1950	3500K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	15	34192	LED15T5/G4/840HE	20	46	2000	4000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	15	34194	LED15T5/G4/850HE	20	46	2000	5000K	80+			50,000	-	Yes	Damp	Requires Driver
<b>Remote 2ft LED Glass T5 HE Tubes (Operates on Remote Driver)</b>																
	G5	15	34196	LED9T5/G2/830HE	20	22.5	1100	3000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	15	34197	LED9T5/G2/835HE	20	22.5	1150	3500K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	15	34204	LED9T5/G2/840HE	20	22.5	1200	4000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	15	34205	LED9T5/G2/850HE	20	22.5	1200	5000K	80+			50,000	-	Yes	Damp	Requires Driver

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
 # UL 1993 Environmental Requirements for LED LAMPS  
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.  
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

## Remote Drivers

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty	Output Current (A)	Frequency	Eff	Output	Output Voltage	Temp (Min)	Temp (Max)	Dimmable	Additional Information
<b>Lightech Drivers - Non-Dimming</b>															
	18	93100	LED9T8/DR/UN/2L	120-277V	10	0.27x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)	
	24	76289	LED12T8/DR/2L	120-277V	10	0.21x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes	
	30	38970	LED15T8/DR/UN/2L	120-277V	10	0.44x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)	
	36	82347	LED18T8/DR/UN/2L	120-277V	10	0.53x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)	
	21	94384	LED21T8/DR/1L	120-277V	10	0.62	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 1 Tube	
	42	94385	LED21T8/DR/2L	120-277V	10	0.62x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes	
<b>Lightech Drivers - Dimming</b>															
	24	76290	LED12T8/DR/D2L	120-277V	10	0.21x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	48	76318	LED12T8/DR/D4L	120-277V	10	0.21x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes	
	42	28174	LED14/DR/D3L	120-277V	10	0.43x3	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 3 Tubes	
	30	38974	LED15T8/DR/D2L	120-277V	10	0.44x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	60	38975	LED15T8/DR/D4L	120-277V	10	0.44x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes	
	36	88141	LED18T8/DR/D2L	120-277V	10	0.53x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	72	88139	LED18T8/DR/D4L	120-277V	10	0.53x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes	
	42	60041	LED21T8/DR/D2L	120-277V	10	0.62x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	84	62030	LED21T8/DR/D4L	120-277V	10	0.62x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes	
	45	34016	LED21T8/DR/VLC2L	120-277V	10	0.62x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	72	63126	LED36T8/DR/D2L	120-277V	10	1.06x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	144	92013	LED36T8/DR/D4L	120-277V	10	1.06x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tube	

### Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
 # UL 1993 Environmental Requirements for LED LAMPS

- Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
- Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
- Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

**current**  
powered by GE

All trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. Current, powered by GE is a business of the General Electric Company.  
© 2018 GE.



<http://products.currentbyge.com> | LEDL046 (Rev 01 /31/18)